

| <b>Part name</b>        | <b>German name</b>      | <b>Drawing nr.</b> | <b>Swiss material</b>          | <b>German material</b> | <b>Used for Mauser Parabellum</b> |
|-------------------------|-------------------------|--------------------|--------------------------------|------------------------|-----------------------------------|
| Frame                   | Griffstuck              | 1000,01,00         | E 26                           | EC Mo 80               | CK 45                             |
| Trigger                 | Abzug                   | 1000,02,00         | E 25                           | 14 Ni Cr 14            | C 15                              |
| Trigger spring          | Druckf. Z. Abz.         | 1000,03,00         | FD 09                          | --                     | Federstahldraht II                |
| Takedown lever          | Riegel                  | 1000,04,00         | E 25                           | 14 Ni Cr 14            | C 15                              |
| Takedown lever spring   | Riegelfeder             | 1000,05,00         | F 27                           | 50 Cr V 4              | wahlw. GS-CK 16 x 12 Cr Ni 177    |
| Safety lever            | Sperrhebel              | 1000,06,00         | --                             | 50 Cr V 4              | 50 Cr V4                          |
| Main spring             | Schliessfeder           | 1000,07,00         | FD 09                          | --                     | Federstahldraht                   |
| Magazine catch          | Magazinhalter           | 1000,09,00         | E 25                           | 14 Ni Cr 14            | 16 Mn Cr 5                        |
| Main spring bar         | Zugstange               | 1000,08,00         | E 25                           | 14 Ni Cr 14            | 50 Cr V4                          |
| Magazine catch spring   | Magazinhalterfeder      | 1000,10,00         | FB 07                          | C 67 G                 | 50 Cr V4                          |
| Sear bar safety hook ke | Zylindst.f.Zugst.-W.    | 1000,11,00         | S S 0                          | C 115 W 2              | C 60                              |
| Grip safety spring      | Feder z.Sicherungsh.    | 1000,12,00         | FB 07                          | C 67 G                 | 50 Cr V4                          |
| Light trigger spring    | Abzugf.f.Leicht.Druckp. | 1000,13,00         | FD 09                          | --                     | Federstahldraht II                |
| Grip screw              | Griffschalenschraube    | 1000,17,00         | A 0                            | 9 S 20 K               | 9 S 20 K                          |
| Grip plate,left         | Griffschale, links      | 1000,14,00         | Kunsth.-Prod. M. Stoffeinlagen | Nussbaumholz           | Nussbaumholz                      |
| Grip plate, right       | Griffschale, rechts     | 1000,15,00         | Kunsth.-Prod. M. Stoffeinlagen | Nussbaumholz           | Nussbaumholz                      |
| Hold-open lever         | Verschlussfanggelenk    | 1100,01,00         | E 25                           | 14 Ni Cr 14            | C 60                              |
| Hold-open lever spring  | Feder z. Verschl.f.Gel. | 1100,02,00         | FB 07                          | C 67 G                 | 50 Cr V4                          |
| Grip safety             | Sicherungshebel         | 1200,01,00         | B 03 60                        | --                     | RSt 1304                          |
| Grip safety pin         | Stift z. Sicherg.-H     | 1200,02,00         | M 02                           | --                     | C 60                              |
| Recoil lever            | Zugst.-Winkelhebel      | 1300,01,00         | E 25                           | 14 Ni Cr 14            | C 60                              |
| Recoil lever pin        | Nietstift               | 1300,02,00         | S S 0                          | C 115 W 2              | C 60                              |
| Ejector                 | Auswerfer               | 2000,01,00         | F 27 V 70                      | 50 Cr V 4              | C 60                              |
| Sear spring             | Abzugst.-Feder          | 2000,02,00         | FB 06                          | CK 67 G                | 50 Cr V4                          |
| Toggle and receiver cor | Verschlussbolzen        | 2000,03,00         | F 27                           | 50 Cr V 4              | C 60                              |
| Front sight             | Korn                    | 2000,06,00         | V 04                           | 36 Cr Ni Mo 4          | C 60                              |
| Receiver                | Gabelgehäuse            | 2100,01,00         | E 25                           | 14 Ni Cr 14            | 16 Mn Cr 5                        |
| Barrel                  | Lauf                    | 2100,02,00         | V 35                           | 36 Cr Ni Mo 4          | 42 Cr Mo 4                        |
| Sear bar                | Abzugstange             | 2200,01,00         | E 25                           | 14 Ni Cr 14            | 16 Mn Cr 5                        |
| Sear bar plunger spring | Schnappstiftfeder       | 2200,02,00         | FD 09                          | --                     | Federstahldraht II                |
| Sear bar plunger        | Schnappstift            | 2200,03,00         | S S 1                          | 115 Cr V 3             | C 60                              |
| Sear bar plunger pin    | Schnappstiftniet        | 2200,05,00         | S S 0                          | C 115 W 2              | C 60                              |
| Front toggle pin        | Vordergelenkstift       | 2300,01,00         | F 27                           | 50 Cr V 4              | C 60                              |
| Firing pin              | Schlagbolzen            | 2400,01,00         | E 25                           | 14 Ni Cr 14            | 16 Mn Cr 5                        |
| Firing pin spring       | Schlagbolzenfeder       | 2400,02,00         | FD 09                          | --                     | Federstahldraht II                |

|                           |                        |            |             |             |                                   |
|---------------------------|------------------------|------------|-------------|-------------|-----------------------------------|
| Fring pin spring retainer | Bodenstuck             | 2400,03,00 | F 27        | 50 Cr V 4   | 16 Mn Cr 5                        |
| Breechblock               | Kammer                 | 2500,01,00 | E 25        | 14 Ni Cr 14 | 16 Mn Cr 5                        |
| Extractor spring          | Auszieherfeder         | 2500,02,00 | FD 09       | --          | Federstahldraht II                |
| Extractor                 | Auszieher              | 2500,03,00 | F 27        | 50 Cr V 4   | 50 Cr V4                          |
| Extractor pin             | Auszieherstift         | 2500,04,00 | S S 0       | C 115 W 2   | C 60                              |
| Front toggle              | Vordergelenk           | 2600,01,00 | E 25        | 14 Ni Cr 14 | 16 Mn Cr 5                        |
| Rear toggle pin           | Hintergelenkstift      | 2600,02,00 | F 27        | 50 Cr V 4   | C 60                              |
| Rear toggle               | Hintergelenk           | 2700,01,00 | E 25        | 14 Ni Cr 14 | 16 Mn Cr 5                        |
| Connecting link           | Kette                  | 2700,02,00 | E 25        | 14 Ni Cr 14 | 50 Cr V4                          |
| Connecting link pin       | Kettenniet             | 2700,03,00 | S S 1       | 115 Cr V 3  | C 60                              |
| Side plate                | Deckplatte             | 3000,01,00 | E 25        | 14 Ni Cr 14 | 16 Mn Cr 5                        |
| Trigger lever             | Abzugswinkelhebel      | 3000,02,00 | E 25        | 14 Ni Cr 14 | C 60                              |
| Trigger lever pin         | Abzugswinkelhebelstift | 3000,03,00 | S S 1       | 115 Cr V 3  | C 60                              |
| Magazine body             | Magazinrohr            | 4000,01,00 | B 00 60     | --          | Gurtgliederstahl                  |
| Magazine follower         | Patronenzubringer      | 4000,03,00 | E 25        | 14 Ni Cr 14 | Sintermetall C 11                 |
| Magazine spring guide     | Zubringerkopf          | 4000,04,00 | M 02        | St 42 K     | C 60                              |
| Magazine button           | Drukknopf z. Magazin   | 4000,05,00 | A1          | A1          | MS 58 F 44                        |
| Magazine spring           | Zubringerfeder         | 4000,06,00 | FD 09 p 255 | --          | Federstahldraht II                |
| Magazine bottom           | Bodenstuck             | 4000,06,00 | Pressstoff  | Pressstoff  | Celidor od. Noryl sch. *)         |
| Magazine bottom pin       | Bodenstuckstift        | 4000,08,00 | S S 0       | C 115 W 2   | Knebelkerbstift 2,5 x 12 DIN 1473 |
| Cleaning rod              | Wischstock             | 0000,01,00 | --          | --          | verz. Eisedraht m. Borsten        |
| Loading tool              | Schraubenzieher        | 0000,02,00 | --          | --          | C 45 W 3                          |

\*) Celidor is Cellulose Polypropionate

\*\*)Noryl is a blend of polyphenylene



э, registered product name by Bayer.

oxide (PPO) and polystyrene that was developed by General Electric Plastics in 1966